

SALIENT FEATURES



- Provides high voltage correction rate against wide range of input voltage.
- High reliability due to no semi conductor or moving parts.
- Excellent spike, Surge Suppression.
- Output Load is isolated from Input mains.
- Short circuit and overload protection.
- Minimum maintenance.

CERTIFICATION

- RoHS
- OHSAS 18001
- ISO 9001
- ISO 14001

Address : 66 Salkia School Road, 'AAVAS', B Block, Howrah - 711 106

Phone : 8420007562

E-Mail : service@epochelectronica.com



EPOCH Electronica Ltd.

TECHNICAL SPECIFICATIONS FOR **CONSTANT VOLTAGE TRANSFORMER**

Standard Rating	500 VA to 5000 VA
Input Voltage	130V-280V Single Phase AC
Line Frequency	50Hz
Output Voltage	220-230V $\pm 1\%$
Effeciency	90% (approx.) under full load condition
Output Wave Form	Sinewave
Load Regulation	$\pm 5V$
Voltage Indication	Analog Voltmeter
Ambient Temperature	-10 degree centigrade to 50 degree centigrade
Transformer Type	Ferro-Resonant

Address : 66 Salkia School Road, 'AAVAS', B Block, Howrah - 711 106

Phone : 8420007562

E-Mail : service@epochelectronica.com